

SERIES: SWI100C-N | DESCRIPTION: AC-DC POWER SUPPLY

FEATURES

- up to 100 W continuous power
- fixed or flip NA AC blade
- level VI efficiency
- universal input voltage range
- integrated USB type C Port
- USB power delivery (PD) 3.0 and PPS compliant
- UL 62368-1 certified
- custom designs available




MODEL

MODEL		output voltage	output current max	output power max	ripple and noise ¹ max	efficiency level
		(Vdc)	(A)	(W)	(mVp-p)	
SWI100C-P-N	fixed	5	3	15	200	VI
		9	3	27	300	VI
		12	3	36	300	VI
		15	3	45	300	VI
		20	5	100	300	VI
	programmable	3.3~21	5	100	300	VI

Notes: 1. At full load, 25°C, at 115/230 Vac input, 20 MHz bandwidth oscilloscope, output terminated with 0.1 µF and 10 µF capacitors.

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
voltage		90	100~240	264	Vac
frequency		47	50~60	63	Hz
current				1.5	A
inrush current	at 230 Vac, 25°C			100	A
leakage current	at 240 Vac			0.25	mA
no load power consumption	at 230 Vac, no load			0.15	W

OUTPUT

parameter	conditions/description	min	typ	max	units
line regulation			±1		%
load regulation	10% ~ 100% rated load		±5		%
start-up time	at 100 ~ 240 Vac, rated load			3	s
rise time	at 115 & 230 Vac, full load			50	ms
hold-up time	at 120 Vac/60 Hz, full load	10			ms

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	auto recovery, hiccup				
	5 Vdc output		7.5		V
	9 Vdc output		13.0		V
	12 Vdc output		16.0		V
	15 Vdc output		20.0		V
	20 Vdc output		25.0		V
over current protection	auto recovery				
	20 Vdc output			6.5	A
	all other outputs			3.9	A
short circuit protection	auto recovery				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output for 1 minute, 10 mA max		3,000		Vac
	input to output for 2 seconds, 10 mA max		3,600		Vac
safety approvals	certified to 62368-1: UL/cUL				
EMI/EMC	FCC				
ESD	EN61000-4-2 contact: 4 kV, air: 8 kV, perf. Criteria A				
radiated immunity	EN61000-4-3 3 V/m, 80% AM (1KHz), perf. Criteria A				
EFT/burst	EN61000-4-4 line to line: 1 kV, line to earth: 1 kV, perf. Criteria A				
surge	EN61000-4-5 line to line: 1 kV, line to earth: 1 kV, perf. Criteria A				
conducted immunity	EN61000-4-6 3 Vrms, 80% AM (1KHz), perf. Criteria A				
MTBF	as per Telcordia SR-332 Issue 3 (2011), at 25°C	300,000			hours
RoHS	yes				

ENVIRONMENTAL


parameter	conditions/description	min	typ	max	units
operating temperature		-10		40	°C
storage temperature		-20		80	°C
operating humidity	non-condensing	20		98	%
storage humidity	non-condensing	20		98	%
altitude				2,000	m

MECHANICAL


parameter	conditions/description	min	typ	max	units
dimensions	63.0 x 61.5 x 30.0				mm
inlet plug	North America, 2-pin				
DC output	USB Type C				
weight	tolerance ±5%		195.9		g

MECHANICAL DRAWING

units: mm



DC CORD



Plugs: USB-C to USB-C
Length: 1,000/1,500 mm
Color: black/white

REVISION HISTORY

rev.	description	date
1.0	initial release	07/03/2026

The revision history provided is for informational purposes only and is believed to be accurate.



15575 SW Sequoia Pkwy #100
Portland, OR 97224
800.275.4899

Fax 503.612.2383
Belfuse.com
powersupport@belf.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.