

DESCRIPTION: INTERNAL AC-DC POWER SUPPLY SERIES: VOFM-150E

FEATURES

- 100 W with natural convection, 150 W with forced air cooling
- 3"x2" compact size, industrial design
- IEC/EN/UL 60601-1 certified
- operating temperature -20°C to 70°C (with derating)
- short-circuit protection, over power protection, overvoltage protection
- 2 x MOPP (BF rated)
- main output power ON LED indicators
- low no load power consumption (<0.150 W)
- chassis mounting



	-				
MODEL	output voltage	output current ¹	output power ^{1,2}	ripple and noise ³	efficiency level⁴
	(Vdc)	max (A)	max (W)	typ (mVp-p)	typ (%)
VOFM-150E-12	12	12.5	150	120	92
VOFM-150E-15	15	10.0	150	150	92
VOFM-150E-18	18	8.34	150	180	92
VOFM-150E-24	24	6.25	150	240	92
VOFM-150E-28	28	5.36	150	280	92
VOFM-150E-36	36	4.17	150	360	92
VOFM-150E-48	48	3.13	150	360	92
VOFM-150E-54	54	2.78	150	360	92

1. With forced air (10 CFM).

Maximum output power is 150 W with 10 CFM forced air cooling, and 100 W with natural convection cooling.
Ripple and noise are measured at oscilloscope 20MHz bandwidth by a 10µF electrolytic capacitor and a 0.1µF ceramic capacitor in parallel at output connector.
At full load, 230 Vac.

PART NUMBER KEY

.....

Notes:



.....

INPUT

parameter	conditio	ns/description	min	typ	max	units
voltage			90	115~230	264	Vac
frequency			47	50~60	63	Hz
current	at 115 Va	ac/50 Hz			2	А
inrush current	at 230 Va	ac, cold start			100	А
leakage current	earth touch	at 264 Vac (Class I) at 264 Vac (Class II)			300 100	μΑ μΑ
no load power consumption					0.15	W
power factor			0.9			

OUTPUT

parameter	conditions/description	min	typ	max	units
	12 Vdc output model			8.34 / 12.5	А
output current	15 Vdc output model			6.67 / 10.0	А
	18 Vdc output model			5.56 / 8.34	А
	24 Vdc output model			4.17 / 6.25	А
(natural convection/forced air ⁵)	28 Vdc output model			3.58 / 5.36	A
	36 Vdc output model			2.78 / 4.17	A
	48 Vdc output model			2.09 / 3.13	A
	54 Vdc output model			1.86 / 2.78	A
land requisition	12, 15, 18, 24, 28 Vdc output models		±3		0/
load regulation	all other output models		±2		%
hold-up time		10			ms
transient response	10% to full load deviation recovery time <20m	IS 10% max			
overshoot	turn-on and turn-off overshoot shall not excee	d $\pm 10\%$ of the volta	ge regula	tion tolerance	
switching frequency	at full load	75		90	kHz
Notes: 5. With forced air 10 CFM.					

PROTECTIONS

parameter	conditions/description	min	typ	max	units
	12 Vdc output, output shut-down with latch	13.2		15.6	Vdc
	15 Vdc output, output shut-down with latch	16.5		19.5	Vdc
	18 Vdc output, output shut-down with latch	19.8		23.4	Vdc
	24 Vdc output, output shut-down with latch	26.4		31.2	Vdc
over voltage protection	28 Vdc output, output shut-down with latch	30.8		36.4	Vdc
	36 Vdc output, output shut-down with latch	39.6		46.8	Vdc
	48 Vdc output, output shut-down with latch	52.8		62.4	Vdc
	54 Vdc output, output shut-down with latch	59.4		64.8	Vdc
over current protection	auto-recovery	105		160	%
short circuit protection	auto-recovery				
over temperature protection	latching type, power recycle				

.....

.....

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output, for 4 seconds (Class I & II) input to frame ground, for 4 seconds (Class I) output to frame ground, for 4 seconds (Class I)	5,656 2,121 2,121			Vdc Vdc Vdc
safety approvals	certified to 60601-1: IEC/EN/UL				
safety class	Class I, Class II				
EMI/EMC	EN55011 Class B & EN60601-1-2 FCC Part 18 Class B				
MTBF	as per Telcordia (Bellcore TR-332) at 25°C	400,000			hours
RoHS	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature		-20		70	°C
storage temperature		-20		85	°C
operating humidity	non-condensing	10		95	%
storage humidity	non-condensing	0		95	%
altitude				5,000	m

DERATING CURVE



TEMPERATURE DERATING CURVE

MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	open frame: 76.2 x 50.8 x 31.0 [3.00 x 2.00 x 1.22 i U-frame: 90.6 x 64.0 x 38.0 [3.57 x 2.52 x 1.50 inch	nch] ı]			mm mm
weight	open frame: U-frame:		150 200		g g
cooling	forced air 10 CFM				

MECHANICAL DRAWING

Open frame

units: mm [inch]







CN1: Input Connector (pitch: 3.96mm) JST B3P-VH-B or equivalent Mates with JST VHR-3N or equivalent					
PIN	PIN Function				
1 AC(L)					
2	AC(N)				

	CN2: Main Output Connector (pitch: 3.96mm / 3.50mm)						
JST B4P-VH-B or equivalent Mates with JST VHR-4N or equivalent JST B4P-VH-B or equivalent I6-24 AWG (1.5mm2) Wire range							
PIN Function		Function					
1 GND		GND					
2	GND	GND					
3	+Vout	+Vout					
4	+Vout	+Vout					

DC FAN Recommended Direction



MECHANICAL DRAWING

U-frame frame

units: mm [inch]



CN1: I Mates	CN1: Input Connector (pitch: 3.96mm) JST B3P-VH-B or equivalent Mates with JST VHR-3N or equivalent				
PIN	Function				
1 AC(L)					
2 AC(N)					

	CN2: Main Output Connector (pitch: 3.96mm / 3.50mm)						
JS Mates	T B4P-VH-B or equivalent with JST VHR-4N or equivalent	Eurostyle P.C.B. 3.50mm Terminal Block 16-24 AWG (1.5mm2) Wire range					
PIN	Function	Function					
1 GND		GND					
2 GND		GND					
3	+Vout	+Vout					
4 +Vout		+Vout					

DC FAN Recommended Direction



.....



REVISION HISTORY

rev.	description	date
1.0	initial release	06/16/2025

The revision history provided is for informational purposes only and is believed to be accurate.



15575 SW Sequoia Pkwy #100 Portland, OR 97224 800.275.4899

.....

Fax 503.612.2383 Belfuse.com powersupport@belf.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.