CUI INC
a bel group

CE

Declaration of Conformity

Manufacturer:
CUI Inc.
15575 SW Sequoia Parkway, Suite 100
Portland, Oregon 97224

For the following equipment:

DC-DC Converter
CUI Series: DQD6-U
Models: 12V, 24V, 48V nominal input, see next page

This declaration of conformity is issued under the sole responsibility of the manufacturer.
The object of the declaration described above is in conformity with the relevant Union harmonization legislations and their amendments:

Low Voltage Directive 2014/35/EU (for product with nominal 48V input)
EMC Directive 2014/30/EU
RoHS Directive 2011/65/EU and (EU) 2015/863

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:

Health & Safety	EN IEC 62368-1:2024+A11:2024
EMC	EN 55032:2015+A1:2020; EN 55035:2017+A11:2020
RoHS	EN IEC 63000:2018

Note: These component level power supplies are intended exclusively for inclusion within other equipment. Protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
The units have been tested and evaluated to the safety requirements of EN IEC 62368-1:2024+A11:2024.
An additional delta evaluation of the above-listed equipment concerning the differences between the requirements of the harmonized standard EN 62368-1:2014 (with all applicable corrections) and EN IEC 62368-1:2024, and IEC 62368-1:2023 has been performed and concludes that the safety objectives of the low-voltage targets (2014/35/EU) are met.

(manufacturer)	**Shenzhen, China** (place)	**08/06/2026** (date)

Link Lu
Product Compliance Specialist

(manufacturer)	**Portland, Oregon, USA** (place)	**08/06/2026** (date)

Editha Vergara
Senior Director, Product Compliance

MODEL LIST

DQD6-xx-Syy-U-zzzzz (where xx = 12, 24, 48 denote nominal input voltage; yy = 3, 5, 9, 12, 15, 24 denote output voltage; zzzzz represent special requirement by different customer, when "zzzzz" is blank, the "-" before "zzzzz" is not displayed)

DQD6-xx-Dyy-U-zzzzz (where xx = 12, 24, 48 denote nominal input voltage; yy = 3, 5, 9, 12, 15, 24 denote output voltage; zzzzz represent special requirement by different customer, when "zzzzz" is blank, the "-" before "zzzzz" is not displayed)

Model	Input voltage (typ.)	Input voltage (range)	Output voltage (Vdc)
DQD6-12-S3-U	12	4.5-18	3.3
DQD6-12-S5-U	12	4.5-18	5
DQD6-12-S9-U	12	4.5-18	9
DQD6-12-S12-U	12	4.5-18	12
DQD6-12-S15-U	12	4.5-18	15
DQD6-12-S24-U	12	4.5-18	24
DQD6-24-S3-U	24	9-36	3.3
DQD6-24-S5-U	24	9-36	5
DQD6-24-S9-U	24	9-36	9
DQD6-24-S12-U	24	9-36	12
DQD6-24-S15-U	24	9-36	15
DQD6-24-S24-U	24	9-36	24
DQD6-48-S3-U	48	18-75	3.3
DQD6-48-S5-U	48	18-75	5
DQD6-48-S12-U	48	18-75	12
DQD6-48-S15-U	48	18-75	15
DQD6-48-S24-U	48	18-75	24
DQD6-12-D3-U	12	4.5-18	±3.3
DQD6-12-D5-U	12	4.5-18	±5
DQD6-12-D9-U	12	4.5-18	±9
DQD6-12-D12-U	12	4.5-18	±12
DQD6-12-D15-U	12	4.5-18	±15
DQD6-12-D24-U	12	4.5-18	±24
DQD6-24-D3-U	24	9-36	±3.3
DQD6-24-D5-U	24	9-36	±5
DQD6-24-D9-U	24	9-36	±9
DQD6-24-D12-U	24	9-36	±12
DQD6-24-D15-U	24	9-36	±15
DQD6-24-D24-U	24	9-36	±24
DQD6-48-D3-U	48	18-75	±3.3
DQD6-48-D5-U	48	18-75	±5
DQD6-48-D9-U	48	18-75	±9
DQD6-48-D12-U	48	18-75	±12
DQD6-48-D15-U	48	18-75	±15
DQD6-48-D24-U	48	18-75	±24
Note: Model name maybe followed by additional characters as described on below model naming configuration.			

Model Naming Configuration

DQD6	-	XX	-	X	XX	-	X
I	-	II	-	III	IV	-	V

I	-	Base Number:	DQD6
II	-	Nom. Input Voltage:	12 =12 V; 24 = 24 V; 48 = 48 V
III	-	Output:	S = single; D = dual
IV	-	Output Voltage:	3 = 3.3 V; 5 = 5 V; 9 = 9 V; 12 = 12 V; 15 = 15 V; 24 = 24 V (prefix with ± when dual outputs)
V	-	Mounting Style:	U = U-Frame

REVISION HISTORY

rev.	description	date
1.0	initial release	08/06/26

The revision history provided is for informational purposes only and is believed to be accurate.