CUI INC
a bel group

CE

Declaration of Conformity

Manufacturer:
CUI Inc.
15575 SW Sequoia Parkway, Suite 100
Portland, Oregon 97224

For the following equipment:

DC-DC Converter
CUI Series: PVQ100W-D
Models: 72V nominal input, see next page

This declaration of conformity is issued under the sole responsibility of the manufacturer.
The object of the declaration described above is in conformity with the relevant Union harmonization legislations and their amendments:

Low Voltage Directive 2014/35/EU
EMC Directive 2014/30/EU
RoHS Directive 2011/65/EU and (EU) 2015/863

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:

Health & Safety	EN 62368-1:2014+A11:2017
EMC	EN 55032:2015+A11:2020; EN 55035:2017+A11:2020
RoHS	EN IEC 63000:2018

Note: These component level power supplies are intended exclusively for inclusion within other equipment. Protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.

	Shenzhen, China	**11/20/2024**
(manufacturer)	(place)	(date)

Link Lu
Product Compliance Specialist

	Portland, Oregon, USA	**11/20/2024**
(manufacturer)	(place)	(date)

Editha Vergara
Global Director, Safety, Environmental

MODEL LIST

PVQ100-O72-SXX-D (where XX = 5, 12, 15, 24, 28 denote output voltage)

Model	Input voltage (typ.)	Input voltage (range)	Output voltage (Vdc)
PVQ100W-O72-S5-D	72	12-160	5
PVQ100W-O72-S12-D	72	12-160	12
PVQ100W-O72-S15-D	72	12-160	15
PVQ100W-O72-S24-D	72	12-160	24
PVQ100W-O72-S28-D	72	12-160	28
PVQ100W-O72-S54-D	72	12-160	54
Note: Model name maybe followed by additional characters as described on below model naming configuration.			

Model Naming Configuration

PVQ100W	**-**	**O**	**XX**	**-**	**S**	**XX**	**X**	**-**	**D**	**X**
I	-		II	-		III	IV		V	VI

I	-	Base Number:	PVQ100W
II	-	Nom. Input Voltage:	72 = 72 V
III	-	Output Voltage:	5 = 5 V; 12 = 12 V; 15 = 15 V; 24 = 24 V; 28 = 28 V; 54 = 54 V
IV	-	REM On/Off Logic:	none = positive N = negative
V	-	Mounting Style:	D = DIP
VI	-	Mounting inserts:	blank = M3x0.5 mounting inserts C = clear screw inserts (Ø 3.2 mm)

REVISION HISTORY

rev.	description	date
1.0	initial release	12/15/22
1.01	Update CUI address, Add model list.	11/20/24

The revision history provided is for informational purposes only and is believed to be accurate.